

66863 - LED 1W 350mA

GELD1DMVE350SL

- ☞ Previous SKU: 901001350U
- ☞ LED 1 DC 350mA Plastic Housing, Potted, Leads Converter (USA Version)
- ☞ Current: DC
- ☞ Designed for IP67
- ☞ Reinforced insulation from input to output
- ☞ Small form factor Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal
- ☞ AC Input
- ☞ Fast Start-Up Time 100-240V Input

GENERAL CHARACTERISTICS

Enclosure Type	Plastic
Ambient Temp [Max]	40 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	60 °C
Storage Temperature	-10 °C
Color	Black
Primary Application	LED in- and outdoor lighting Architectural lighting Orientation Lighting Ambiance lighting Task, Table and Floor lighting
Product Technology	LED
CV/CC	CC
CC/CV Value	350 mA
Efficiency	0.5 %
Output Power (W)	1.4 W
Output Current (A)	0.35 A
Output Voltage[Min]	2 V
Output Voltage[Max]	4 V

PRODUCT INFORMATION

Product Code	66863
Description	GELD1DMVE350SL
Alternative Unit Of Measure	EACH
Standard Package Quantity	45
Ean UPC	043168668637
Standard Package GTIN	00043168668637
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	45
Sales Unit	Each
UCC	043168668637
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168668637
Standard Package GTIN	10043168668634
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168668637

DIMENSIONS

Width	34.0 mm
Height	32.0 mm
Weight	25.0 mm

Lead Color	Qty	Exit	Length (± 1 in.)
Black	1	Top	220mm
White	1	Top	220mm
Red	1	Top	220mm

ELECTRICAL CHARACTERISTICS

Power Factor %	Passive
Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.05 A
Input Voltage Range[Min] (V)	0.03 A
Input Voltage Range[Max]	100 V
Input Current Range (Amperes)	240
Input voltage Range	V V