

Туре	
Project	
Catalog No.	





CATALOG INFORMATION								
MODEL	DIMENSIONS	LAMP	LUMENS*	MAX CONNECTED UNITS	LAMP OPTIONS	FINISH		
SG4-6**	9-3/8"L x 3/4"W x 1-1/4"H	T4 6W	480	10	3000K, 4100K, 6400K,	White		
SG4-8	13-1/2"L x 3/4"W x 1-1/4"H	T4 8W	600		Black, Blue, Green,			
SG4-12	17-1/2"L x 3/4"W x 1-1/4"H	T4 12W	800		Red			
SG4-16	19-1/2"L x 3/4"W x 1-1/4"H	T4 16W	1000					
SG4-20	21"L x 3/4"W x 1-1/4"H	T4 20W	1350					
SG4-22	29"L x 3/4"W x 1-1/4"H	T4 22W	1850					
SG4-24	34-1/2"L x 3/4"W x 1-1/4"H	T4 24W	2150					
SG4-26	40-3/8"L x 3/4"W x 1-1/4"H	T4 26W	2550					
SG4-28	46-1/4"L x 3/4"W x 1-1/4"H	T4 28W	2900					

^{*} Based on 4100K lamps.

^{**} The 6W fixture is not available with a Rocker Switch.

Ordering Instructions	MODEL	SWITCH	1	OUTPUT	_	FINISH	
Examples:	SG4-8	SW	/	30] –	W	With built-in Rocker Switch
	SG4-8		/	30] –	W	Without Rocker Switch

DESCRIPTION

- Sleek Plus T4 fluorescent fixtures are furnished with replaceable lamps, tight-fit direct connectors, stainless steel mounting clips for vertical or horizontal mount, and ribbed acrylic lamp covers.
- · Fixtures butt together reducing dark area to less than 1" and with minimal shadowing when they are connected directly.
- Optional On/Off Rocker Switch that does not increase the length of the fixture as it is located on the side.
- Lamp CRI > 85 with the use of tri-phosphor.
- Functions with all code approved lighting branch circuits, including 15A and 20A, as the fixtures are not limited to any size circuit. The wiring is according to lighting circuit load ratings.
- · The ribbed acrylic diffuser lamp cover fits securely on the housing of the fixture with no light leaks, warping or deformed lens.
- Additional power supply cables, connecting cables, hard wire boxes and replacement lamps are sold separately.

LAMPING:

The T4 lamps (included with fixtures) are energy efficient and long-life with a 16,000 hours rating.

BALLAST:

Rated 100-120VAC 50/60Hz. The fixture features a built-in programmed-start, no flickering, silent electronic ballast. 3-years commercial grade fluorescent ballast warranty.

CONSTRUCTION:

The housing is made of extruded aluminum with white enamel painted finish. Aluminum provides better heat dissipation, and longer fixture and lamp life.

LISTINGS:

UL &CUL Listed.

New York City approval.

FCC Part 18 Listed – tested for in-line and radiated interference.





SG4-xx

MINI FLUORESCENT SLEEK PLUS T4 • 3-WIRE CLASSIC GROUNDED

Туре	
Project	
Catalog No.	

ACCESSORIES

MODEL / DESCRIPTION

MODEL / DESCRIPTION



SG-DC: Direct Connector for end-to-end connection.



SG-MC-45: 45°Mounting Clip



SG-B: Plastic Hard Wire Box with Control Switch

3-5/8"L x 2-1/4"W x 1-3/8"H



SG-PS6: Power Strip with 12 Outlets. Includes (1) Direct Connector (SP-DC)

72"L x 7/8"W x 7/8"H

(Not UL Listed)



SG-BM: Commercial Grade Metal Hard Wire Box. Enables fixtures to be controlled by wall switch 2-3/4"L x 1-3/4"W x 1-3/4"H



SG-CC6: 6" Connecting Cable SG-CC12: 12" Connecting Cable SG-CC24: 24" Connecting Cable SG-CC36: 36" Connecting Cable



SG-BM-SW Commercial Grade Metal Hardwire Box with Switch 3-1/2"L x 2"W x 1-1/8"H



SG-CC6L: 6" Right-Angle Connecting Cable

SG-CC12L: : 12" Right-Angle

Connecting Cable

SG-CC24L: 24" Right-Angle

Connecting Cable

SG-CC36L: 36" Right-Angle

Connecting Cable



SG-MC-VH: Stainless Steel Mounting Clip for Vertical & Horizontal Mount



SG-PC24-WH

Power Cord & 3-Prong Plug - 2' White SG-PC72-W

Power Cord & 3-Prong Plug - 6' White SG-PC72-G

Power Cord & 3-Prong Plug – 6' Gray SG-PC96-W

Power Cord & 3-Prong Plug – 8' White

SG-PC144-W

Power Cord & 3-Prong Plug - 12' White



SG-MC-V: Stainless Steel Mounting Clip for Vertical Mount



SG-PCL: 6' Right Angle Power Cord & Plug - From Back



SG-MC-A: Adjustable Mounting Clip



SG-PCLL: 6' Right Angle Power Cord & Plug - From Front



www.jescolighting.com support@jescolighting.com Tech Support: 855.592.0029

15 Harbor Park Drive Port Washington, NY 11050 Main Line: 800.527.7796 Fax Line: 855.265.5768

219 South 6th Ave City of Industry, CA 91746 Main Line: 855.654.0110 Fax Line: 626.333.2955

10/28/2015