

**66883 - LED 18W 700mA Bottom Feed**

**GELD18DMV700BF**

- ☞ Previous SKU: 901018700BF
- ☞ LED 18 DC 700mA BF Aluminum Housing, Potted, Leads Converter - USA Bottom Feed Version
- ☞ Current: DC
- ☞ Dimmable with Trailing Edge dimmers
- ☞ Designed for IP67
- ☞ Reinforced insulation from input to output
- ☞ High efficiency
- ☞ PFC: > 0.95 Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch Overload regulation, Over voltage protection. Self-resettable
- ☞ AC/DC

**GENERAL CHARACTERISTICS**

Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambience lighting
Product Technology	LED
CV/CC	CC
CC/CV Value	700 mA
Output Power (W)	18 W
Output Current (A)	0.7 A
Output Voltage[Min]	4 V
Output Voltage[Max]	26 V

**PRODUCT INFORMATION**

Product Code	66883
Description	GELD18DMV700BF
Alternative Unit Of Measure	EACH
Standard Package Quantity	24
Ean UPC	043168668835
Standard Package GTIN	00043168668835
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
Sales Unit	Each
UCC	043168668835
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168668835
Standard Package GTIN	10043168668832
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168668835

**ELECTRICAL CHARACTERISTICS**

Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.17 A
Input Voltage Range[Min] (V)	0.09 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	277
Input voltage Range	V V