

66914 - LED 25 DC 12 Converter

GELD25DMV12PU 120

👉 Previous SKU: 901025012PU

GENERAL CHARACTERISTICS

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	75 °C
Storage Temperature	-10 °C
Color	Black
Product Technology	LED
Rated Life Hours-nominal	0 h
CV/CC	CV
CC/CVValue	12 V
Output Power (W)	25 W
Output Current (A)	2 A
Base	Wire terminal

PRODUCT INFORMATION

Product Code	66914
Description	GELD25DMV12PU 120
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168669146
Standard Package GTIN	10043168669143
No Of Items Per Sales Unit	
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	043168669146
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168669146
Standard Package GTIN	00043168669146
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168669146

DIMENSIONS

Remote Mount Distance	140.0 m
-----------------------	---------

ELECTRICAL CHARACTERISTICS

Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	60 Hz
Input Current Range[Min]	0.3 A
Input Voltage Range[Min] (V)	0.1 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	277
Input voltage Range	V V
Rated power (Watts)	0 W